Mastercart SERIES

IPL

Made for life in motion For semi-automated Type B American grips, Type C European grips and Type G fully automated collection.



IDEAL FOR

- Waste, Recycling & Organic collection
- Residential, Commercial, Industrial and Institutional environments



Perfect use by function.

Our wide range of tough and durable carts will support all your requirements for organic, waste and recycling collection.

KEY FEATURES

- IPL's injection process uses high density polyethylene (HDPE) that yields precise design and consistent thicknesses;
- UV stabilized against long-term effects of the sun;
- 100% recyclable;
- Unibody design requires no bolts or holes that could potentially leak;
- Designed for maximum wind stability.

STANDARD COLOURS:



Other colours available upon request. Colours shown may vary slightly from actual product.

Mastercart SERIES

32 GAL. - 120L / 64 GAL. - 240L / 95 GAL. - 360L



FEATURES & HIGHLIGHTS

- Advanced lid hinge design offers a tight seal that keeps pests and weather out, and trash in
- Multilingual user instructions on lid
- Large hot stamped area
- Multicolor hot stamping with company logo
- Injection molding labeling on lid (IML)

- Sequential serial numbers
- RFID technology and/or barcode option for quick identification
- Easy to handle
- Bottom wear strips
- Adapted lips for American and European grips

- Snap on wheels without tools
- Solid steel axle, yellow zinc-plated against corrosion
- Dual TPE-rubber and plastic wheel option
- Durable wear strips will protect the bottom of the bin.

PRODUCTS SPECIFICATIONS

VOLUME	32 U.S. GAL. / 120L (MC1800)		64 U.S. GAL. / 240L (MC1012)		64 U.S. GAL. / 240L (AMC1012)		95 U.S. GAL. / 360L (MC594)		95 U.S. GAL. / 360L (MC462)		95 U.S. GAL. / 360L (AMC720)	
	IN	СМ	IN	СМ	IN	СМ	IN	СМ	IN	СМ	IN	СМ
Depth	21 1/16	53.5	27 1/2	69.9	27 1/2	69.9	34 3/8	87.3	33 3/4	85.7	34 3/8	87.3
Width	19 1/8	48.6	24 1/2	62.2	24 1/2	62.2	25 1/8	63.8	26 1/4	66.7	25 1/8	63.8
Height	37 5/8	95.5	43 1/4	109.9	43 1/4	109.9	44 1/2	113	46 1/4	117.5	44 1/2	113
Wheel diameter	8 – 10	20 – 25	8 - 10 - 12	20 - 25 - 30	8 - 10 - 12	20 - 25 - 30	10 – 12	25 - 30	10 – 12	25 - 30	10 – 12	25 - 30
Standard Axle	5/8	1.58	3/4	1.9	3/4	1.9	3/4	1.9	3/4	1.9	3/4	1.9
	LBS.	KG	LBS.	KG	LBS.	KG	LBS.	KG	LBS.	KG	LBS.	KG
Load rating	130	59	240	109	240	109	335	152	335	152	335	152
Assembly weight	20 to 23	9 to 11	32 to 36	15 to 17	28 to 32	13 to 15	39 to 45	18 to 20	39 to 45	18 to 20	37 to 43	17 to 19

	UNITS								
Stacking	12	11	11	9	7	10			
T/L quantity (53')	1800	1012	1012	594	462	720			
Recycling code	2	2	2	2	2	2			

AVAILABLE OPTIONS



Organic lid



Split option for 64 U.S gal./ 240L & 95 U.S gal. / 360L option



Gravity lock



Rotating metal catch bar Reinforced sealed catch bar for AMC Nestable design with catch bar for AMC



Americain grips



Urbain lid for 95 U.S gal. / 360L option



Proven lid hinge and handle designs



MantisWay latch option for 32 U.S gal. / 120L



Silent Dual TPE-rubber and plastic wheels offered in 10'' & 12''



European grips

Mastercart SERIES 32 GAL. - 120L / 64 GAL. - 240L / 95 GAL. - 360L

OPTIONAL

- RFID-ready compartment
- Reflective stickers
- MantisWay latch (32 U.S gal. / 120 L)
- Gravity lock
- Post-consumer raw material (PCR)
- Vented Lid
- Metal Grating for organic option
- In mold labeling (lid)
- Multicolour hot stamping

WARRANTY

- 10-year limited warranty
- 20-year life expectancy; designed for the worst weather conditions
- The most durable cart in North America
- Meets all American National Standards Institute (ANSI) requirements for safety and litter system compatibility (ANSI Z245.30 and Z245.60)
- Cart is 100% recyclable, Code #2

CERTIFICATIONS

When you choose IPL, you work with a recognized industry leader. IPL was the first plastic injection company to achieve ISO 9001 quality certification in North America. The addition of ISO/TS16949 certification further demonstrates IPL's commitment to quality. These quality initiatives demonstrate our capabilities and know-how.

CONTACT US ipl-plastics.com 1 800 463.0270





